

PRODUCT  
**W15**



**YOUR ATTACHMENT SPECIALIST** - [www.bressel-lade.de](http://www.bressel-lade.de)

Send us a mail to: [info@bressel-lade.de](mailto:info@bressel-lade.de)



**Special: Sideparts, rubber blade**



**Special: 2000mm extension**



**Special: Hydraulic turn function**



The attachment is used for pushing grain, fertilizer, salt or silage. With the optional extensions, you can reach to bigger storage heights.

**INFORMATION**

- With hardened cutting edge (steel 100x16mm)
- Blade with reinforced body
- Blade height 1000mm

**Free selectable colors**

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011

# PUSHING BLADE

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

Width	Weight	Part-No.
2200 mm	245 kg	W15 BA-17
2500 mm	285 kg	W15 BA-21
3000 mm	355 kg	W15 BA-27

## ② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Front hydraulic cat. II	NE-18
Front hydraulic cat. III	NE-19
Wheel- or telescopic loader	NE-51

## ③ SPECIAL EQUIPMENT

2000mm extension (+ 225 kg)	VE-02
3000mm extension (+ 295 kg)	VE-03
4000mm extension (+ 375 kg)	VE-04
Quick-coupler between extension and blade (+ ca. 110 kg)	OZ-G1
Blade hydraulic turnable (left and right) (+ 150 kg)	HY-01
Blade hydraulic tippable (+ 20 kg)	SK-01
Sideparts (for better control of material)	SF-01
Tissued special rubber blade (150x40mm) per meter	S1-11
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

## 😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)