



Sideparts, rubber blade



2000mm extension



Hydraulic turn function



The attachment is used for pushing grain, fertilizer, salt or silage. With the optional extensions, you can reach to bigger storage heights.

INFORMATION

- With hardened cutting edge (steel 100x16mm)
- Blade with reinforced body
- Blade height 1000mm

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011

PUSHING BLADE

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Weight	Part-No.
2200 mm	245 kg	W15 BA-17
2500 mm	285 kg	W15 BA-21
3000 mm	355 kg	W15 BA-27

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Front hydraulic cat. II	NE-18
Front hydraulic cat. III	NE-19
Wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

2000mm extension (+ 225 kg)	VE-02
3000mm extension (+ 295 kg)	VE-03
4000mm extension (+ 375 kg)	VE-04
Quick-coupler between extension and blade	OZ-G1
Blade hydraulic turnable (left and right)	HY-01
Blade hydraulic tippable	SK-01
Sideparts (for better control of material)	SF-01
Tissued special rubber blade (150x40mm) per m.	S1-11
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)