




Special: Sideparts, rubber blade



Special: 2000mm extension



The attachment is used for pushing grain, fertilizer, salt or silage. With the optional extensions, you can reach to bigger storage heights.





INFORMATION

- With hardened cutting edge (steel 100x16mm)
- Blade with reinforced body
- Blade height 1000mm



PUSHING BLADE

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS $\mathbf{0} + \mathbf{2} + \mathbf{3} = \mathbf{9}$

CHOOSE PRODUCT		
Width	Weight	Part-No.
2200 mm	245 kg	W15 BA-17
2500 mm	285 kg	W15 BA-21
3000 mm	355 kg	W15 BA-27

2 LOADER QUICK COUPLER (INDICATE BRAND & TYPE)		
Euro-System	AF-M4	
Frontloader without Euro-coupling system	NE-02	
Front hydraulic cat. II	NE-18	
Front hydraulic cat. III	NE-19	
Wheel- or telescopic loader	NE-51	
Please indicate ALWAYS manufacturer and type of the loader on inquiries or orders!		

SPECIAL EQUIPMENT	
Color RAL 7043 - grey	FA-02
Color RAL 9005 - black	FA-03
2000mm extension (+ 225 kg)	VE-02
3000mm extension (+ 295 kg)	VE-03
4000mm extension (+ 375 kg)	VE-04
Quick-coupler between extension and blade (+ ca. 110 kg)	OZ-G1
Blade hydraulic turnable (left and right +/- 25°) (+ 150 kg)	HY-01
Blade hydraulic tippable (+ 20 kg)	SK-01
Sideparts (for better control of material)	SF-01
Tissued special rubber blade (150x40mm) per meter	S1-11
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

9 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)