




The side tip bucket can be unladen by tipping it to the side. There is no loss by unloading height. Further it allows to fill small size drilling machines, salt spreaders, aso.

Basic equipment



Rear view



Tipped



INFORMATION

- Qualified for loading of pour loading goods with max. weight of 1800kg/m³
- Highwear resistant cutting edge (150x20mm, 500HB) with strong substructure (The cutting edge is 150mm smaller than the width of the bucket)
- Bucket height 800mm, Bucket depth 1000mm
- 1 hydraulic cylinder (max. Hydraulic pressure 220 Bar)
- Tipping to right side (90°)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



SIDE TIP BUCKET

for loader from 1,5 to 4,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	ca. theo.	Weighth	Part-No.
1600 mm	670 l	0,83 m ³	575 kg	L75 BA-11
1800 mm	770 l	0,95 m ³	615 kg	L75 BA-13
2000 mm	860 l	1,07 m ³	650 kg	L75 BA-15
2200 mm	960 l	1,19 m ³	690 kg	L75 BA-17
2400 mm	1060 l	1,31 m ³	725 kg	L75 BA-19

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheelloader with Z-bar Kinematic	NE-59
Wheel- and telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Sticked gravel tines (per piece)	SZ-
Protection tube	SS-01
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)