

PRODUCT  
**D45-D46**



**YOUR ATTACHMENT SPECIALIST** - [www.bressel-lade.de](http://www.bressel-lade.de)  
Send us a mail to: [info@bressel-lade.de](mailto:info@bressel-lade.de)



The Silagefork with grapple is strong designed and can be used for tearing out manure or silage out of the stock. This machine is used for many different works on the farms.

**Long version type L**



**Short version type m**



**Type L with push-off wall**



**INFORMATION**

- Thick material main tubes with welded cones
- High value full material tines
- Twist protected tines in the grapple
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)

**Shortversion Typ M** [Product D45]

- Normal load tines 800mm long
- Opening width ca. 1200mm

**Longversion Typ L** [Product D46]

- Heavy duty tines 1000mm long
- Opening width ca. 1300mm

**Free selectable colors**

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



# SILAGE FORK WITH GRAPPLE M/L

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

Type / width	Tines	Volume	Weight	Part-No.
M 1300mm, normal load	7x800mm NL	1050 l	310 kg	D45 BA-08, N8-10
M 1500mm, normal load	8x800mm NL	1220 l	360 kg	D45 BA-10, N8-10
M 1700mm, normal load	9x800mm NL	1380 l	410 kg	D45 BA-12, N8-10
M 1900mm, normal load	10x800mm NL	1540 l	460 kg	D45 BA-14, N8-10
M 2100mm, normal load	11x800mm NL	1700 l	510 kg	D45 BA-16, N8-10
M 2300mm, normal load	12x800mm NL	1860 l	560 kg	D45 BA-18, N8-10
M 1300mm, heavy duty	7x800mm SL	1050 l	335 kg	D45 BA-08, N8-11
M 1500mm, heavy duty	8x800mm SL	1220 l	385 kg	D45 BA-10, N8-11
M 1700mm, heavy duty	9x800mm SL	1380 l	425 kg	D45 BA-12, N8-11
M 1900mm, heavy duty	10x800mm SL	1540 l	480 kg	D45 BA-14, N8-11
M 2100mm, heavy duty	11x800mm SL	1700 l	530 kg	D45 BA-16, N8-11
M 2300mm, heavy duty	12x800mm SL	1860 l	585 kg	D45 BA-18, N8-11
M 2500mm, heavy duty	13x800mm SL	2020 l	585 kg	D45 BA-21, N8-11
L 1700mm, heavy duty	9x1000mm SL	1700 l	560 kg	D46 BA-12, N8-11
L 1900mm, heavy duty	10x1000mm SL	1900 l	590 kg	D46 BA-14, N8-11
L 2100mm, heavy duty	11x1000mm SL	2100 l	620 kg	D46 BA-16, N8-11
L 2300mm, heavy duty	12x1000mm SL	2300 l	650 kg	D46 BA-18, N8-11
L 2500mm, heavy duty	13x1000mm SL	2500 l	680 kg	D46 BA-21, N8-11
L 2700mm, heavy duty	14x1000mm SL	2700 l	710 kg	D46 BA-23, N8-11

## ② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheel- or telescopic loader	NE-51

## ③ SPECIAL EQUIPMENT

1 bowed tine 600mm at every side	ZS-01
Hydraulic push-off wall (max. 1900mm width, +160kg, +1xDA, needed)	AW-02s
Hydraulic push-off wall (over 1900mm width, +200kg, +1xDA, needed)	AW-02b
Electric switch valve 12V/90l (without cable and switch)	UV-02
Automatic switch valve	UV-08
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

## 😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)