



The Silagefork with grapple XL is strong designed and can be used for tearing out manure or silage out of the stock. This machine is used for many different works on the farms.

Standard equipment**Special: Push-off wall****Rear view****INFORMATION**

- Thick material main tubes with welded cones
- High value heavy duty material tines, 1250mm length
- Twist protected tines in the grapple
- With 2 tines at every side
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 1700mm
- With latticed back part



SILAGE FORK WITH GRAPPLE XL

for loader from 5 to 8tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Tines	Volume	Weight	Part-No.
2300 mm	12	3000 l	1050 kg	D50 BA-18
2500 mm	13	3250 l	1120 kg	D50 BA-21
2700 mm	14	3500 l	1190 kg	D50 BA-23
2900 mm	15	3750 l	1260 kg	D50 BA-25

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Wheel- or telescopic loader

Please indicate **ALWAYS** manufacturer and type of the loader on inquiries or orders!

③ SPECIAL EQUIPMENT

■ Color RAL 7043 - grey	FA-02
■ Color RAL 9005 - black	FA-03
Hydr. push off wall till 2300mm width (+ 320kg, +1 x DA needed)	AW-02s
Hydr. push off wall above 2300mm width (+350kg, +1 x DA needed)	AW-02b
Switch valve 12V / 90l (without cable and switch)	UV-02
Switch valve 12V / 120 (without cable and switch)	UV-03
Switch valve 24V / 90l (without cable and switch)	UV-05
Switch valve 24V / 120l (without cable and switch)	UV-06
Automatic switch valve	UV-08
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)