



Basic equipment



Function



The Silage rake is used for pulling down the silage out of high silage stocks. It is also used for rake down the silage from the silage stock and load it with a light material bucket.

Tine tube



INFORMATION

- Thick material main tube with welded cones (twist protected)
- With 7 high value full profile hardened tines
- Tine length 800mm heavy duty

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



SILAGE RAKE

for loader from 1,5 to 10tons lifting capacity

A PERFECT ATTACHMENT IN 2 STEPS ① + ② = 😊

① CHOOSE PRODUCT

Width	Extension	Weight	Part-No.
2350 mm	1500 mm	305 kg	S85 OZ-80
2350 mm	2500 mm	345 kg	S85 OZ-81
2350 mm	4000 mm	695 kg	S85 OZ-83
2350 mm	5000 mm	795 kg	S85 OZ-84

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheel- or telescopic loader	NE-51
Excavator Lehnhoff MS08	NE-70

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)