



The Silagebucket is designed for collection and transportation of chopped silage.

**Basic equipment**



**Special: Screwed turnable knife**



**Special: Automatic greasing**



**INFORMATION**

- Bucket depth 1200mm, bucket height 1200mm
- With 2 sickle reinforcements
- Reinforced body
- With high wear resistant substructure and cutting edge (200x20mm, 500HB)
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 2000mm
- Thick material main tube with welded cones
- With 3 tines at every side



# SILAGEBUCKET A XXL

for loader from 5,5 to 8tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

Width	Volume	Tines	Weight	Part-No.
2400 mm	3450 l	10	1590 kg	S80 BA-19
2600 mm	3750 l	12	1690 kg	S80 BA-22
2800 mm	4000 l	13	1780 kg	S80 BA-24
3000 mm	4250 l	14	1880 kg	S80 BA-27

## ② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

Please indicate **ALWAYS** manufacturer and type of the loader on inquiries or orders!

## ③ SPECIAL EQUIPMENT

<input type="checkbox"/> Color RAL 7043 - grey	FA-02
<input type="checkbox"/> Color RAL 9005 - black	FA-03
Raised sideparts	SH-03
High wear resistant cutting edge (300x30mm, 500HB) <b>-per Meter</b>	S3-05
Screwed knife (dbl. beveled, 250x25mm, 500HB) <b>-per Meter</b>	S3-20
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

## 😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)