



*The Silagebucket is designed for collection and transportation of silage and loading of manure.*

#### S45 Basic equipment



#### S46



#### S47 High tip function



#### INFORMATION

- With highwear resistant cutting edge (150x20mm, 500HB)
- With strong substructure with several wear stripes
- Bucket height 650mm, bucket depth 850mm
- With 1 (above 2000mm 2) sickle reinforcements
- With 2 hydraulic cylinders (max. 220 bar)
- Opening width 1250mm
- Grapple with 2 (above 2000mm 4) bearings
- With side sickles for reduced transport losses (not for S46)



# SILAGEBUCKET S M

for loader from 1,5 to 3,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT





Width	Volume	Tines	Weight	Teile-Nr.
1350 mm	675 l	4	540 kg	S45 BA-A8
1500 mm	790 l	4	560 kg	S45 BA-10
1650 mm	840 l	4	605 kg	S45 BA-A1
1800 mm	925 l	5	620 kg	S45 BA-13
2000 mm	1040 l	5	670 kg	S45 BA-15
2200 mm	1140 l	6	745 kg	S45 BA-17
2400 mm	1250 l	6	790 kg	S45 BA-19
2600 mm	1350 l	7	835 kg	S45 BA-22
2800 mm	1440 l	7	880 kg	S45 BA-24

## ② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System (min. 1650mm width)	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

Please indicate **ALWAYS** manufacturer and type of the loader on inquiries or orders!

## ③ SPECIAL EQUIPMENT

 Color RAL 7043 - grey	FA-02
 Color RAL 9005 - black	FA-03
 Color similar to MF red	FA-10
 Color similar to John Deere green	FA-07
Grapple opens behind the cutting edge (without side sickles)	S46
Removable bucket sideparts (screwed)	SH-02
High wear res. substruc. and cutting edge (200x20mm, 500HB) <b>-per Meter</b>	S2-03
Screwed knife (dbl. bevelled, 200x20mm, 500HB) <b>-per Meter</b>	S2-06
High tip function (1650mm width, + 350kg, + 1x DA needed)	S47s
High tip function (1800 and 2000mm width, + 350kg, + 1x DA needed)	S47m
High tip function (above 2000mm width, + 350kg, + 1x DA needed)	S47l
Switch valve 12V / 90l in connection with high tip function	UV-02
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01
With Kramer Smart-Attach Coupler (min. 2m width, only 1 DA)	QK-15

## 😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)