



The Silagebucket is designed for collection and transportation of silage and loading of manure.

S55 Basic equipment



S56 More bucket depth



S57 High tip function



INFORMATION

- With highwear resistant cutting edge (200x20mm, 500HB)
- High wear resistant substructure with several wear stripes (500HB)
- Bucket height 900mm, bucket depth 1100mm
- With 2 sickle reinforcements
- With 2 hydraulic cylinders (max. 220 bar)
- Opening width 1550mm
- Grapple with 4 bearings
- With side sickles for reduced transport losses



SILAGEBUCKET S XL

for loader from 3,5 to 5,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	Tines	Weight	Part-No.
2200 mm	2200 l	6	1145 kg	S55 BA-17
2400 mm	2400 l	6	1195 kg	S55 BA-19
2600 mm	2600 l	7	1275 kg	S55 BA-22
2800 mm	2800 l	7	1325 kg	S55 BA-24

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

Please indicate **ALWAYS** manufacturer and type of the loader on inquiries or orders!

③ SPECIAL EQUIPMENT

<input type="checkbox"/> Color RAL 7043 - grey	FA-02
<input type="checkbox"/> Color RAL 9005 - black	FA-03
High wear resistant cutting edge (300x30mm, 500HB) per meter	S3-05
Screwed knife (dbl. beveled, 250x25mm, 500HB) per meter	S3-20
High tip function (+ 390kg, + 1x DA needed)	S57
Switch valve 12V / 120l in connection with high tip function	UV-04
Switch valve 24V / 120l in connection with high tip function	UV-06
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)