



Basic equipment



Basic equipment



Special: High-tip function



The Silagebucket is designed for collection and transportation of chopped silage.

INFORMATION

- With highwear resistant cutting edge (150x20mm, 500HB)
- With strong substructure
- Bucket height 800mm, bucket depth 1000mm
- With 1 respectively 2 sickle reinforcements
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 1250mm
- Thick material main tube with welded cones (twist protected)
- Length of tines 600mm
- With 1 tine 600mm at every side

Free selectable colors





SILAGEBUCKET TYPE A L

for loader from 2,5 to 4,5 tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	Tines	Weight	Part-No.
1600 mm	1280 l	7	735 kg	S70 BA-11
1800 mm	1420 l	8	780 kg	S70 BA-13
2000 mm	1580 l	9	845 kg	S70 BA-15
2200 mm	1740 l	10	900 kg	S70 BA-17
2400 mm	1900 l	10	960 kg	S70 BA-19
2600 mm	2050 l	11	1015 kg	S70 BA-22
2800 mm	2200 l	13	1070 kg	S70 BA-24

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

High wear res. substruc. and cutting edge (200x20mm, 500HB) per meter	S2-03
Screwed knife (dbl. bevelded, 200x20mm, 500HB) per meter	S2-06
Heavy duty tines in the grapple (per tine)	N8-11
High tip function (1800 and 2000mm width, + 350kg, + 1x DA needed)	S72m
High tip function (above 2000mm width, + 350kg, + 1x DA needed)	S72l
Switch valve 12V / 90l in connection with high tip function	UV-02
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)