

PRODUCT
S75



YOUR ATTACHMENT SPECIALIST - www.bressel-lade.de
Send us a mail to: info@bressel-lade.de



The Silagebucket type A XL is designed for collection and transportation of chopped silage.

**Special: Side parts,
screwed knife**



Basic equipment



**Special: S77 - High tip
function**



INFORMATION

- Bucket height 900mm, bucket depth 1100mm
- With 2 sickle reinforcements
- With high wear resistant substructure and cutting edge (200x20mm, 500HB)
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 1550mm
- Thick material main tube with welded cones (twist protected) and full-material heavy duty tines 800mm length
- With 2 tines at every side

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



SILAGEBUCKET TYPE A XL

for loader from 3,5 to 5,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	Tines	Weight	Part-No.
2200 mm	2200 l	10	1200 kg	S75 BA-17
2400 mm	2400 l	10	1250 kg	S75 BA-19
2600 mm	2600 l	11	1300 kg	S75 BA-22
2800 mm	2800 l	13	1350 kg	S75 BA-24

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Raised sideparts (convex form, screwed)	SH-03
High wear resistant cutting edge (300x30mm, 500HB) per meter	S3-05
Screwed knife (dbl. beveled, 250x25mm, 500HB) per meter	S3-20
High tip function (+ 390kg, + 1x DA needed)	S77
Switch valve 12V / 120l in connection with high tip function	UV-04
Switch valve 24V / 120l in connection with high tip function	UV-06
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)