



The Silagebucket is designed for collection and transportation of chopped silage.

Basic equipment



Special: Screwed turnable knife



Special: Automatic greasing



INFORMATION

- Bucket depth 1200mm, bucket height 1200mm
- With 2 sickle reinforcements
- Reinforced body
- With high wear resistant substructure and cutting edge (200x20mm, 500HB)
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 2000mm
- Thick material main tube with welded cones
- With 3 tines at every side

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



SILAGEBUCKET TYPE A XXL

for loader from 5,5 to 8tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

| Width | Volume | Tines | Weight | Part-No. |
|---------|--------|-------|---------|-----------|
| 2400 mm | 3450 l | 10 | 1590 kg | S80 BA-19 |
| 2600 mm | 3750 l | 12 | 1690 kg | S80 BA-22 |
| 2800 mm | 4000 l | 13 | 1780 kg | S80 BA-24 |
| 3000 mm | 4250 l | 14 | 1880 kg | S80 BA-27 |

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

| | |
|---------------------------------------|-------|
| Wheelloader with Z-bar Kinematic | NE-59 |
| All other wheel- or telescopic loader | NE-51 |

③ SPECIAL EQUIPMENT

| | |
|--|-------|
| Raised sideparts (convex form, screwed) | SH-03 |
| High wear resistant cutting edge (300x30mm, 500HB) per meter | S3-05 |
| Screwed knife (dbl. beveled, 250x25mm, 500HB) per meter | S3-20 |
| Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.) | DH-01 |

😊 READY (ALL PRICES +7,5% SURCHARGE)

| |
|--|
| Delivery FCA at factory Visselhövede (Transportcosts on request) |
|--|