



The Silagebucket is designed for collection and transportation of silage and loading of manure.

Basic equipment



Basic equipment



Optional automatic greasing



INFORMATION

- With highwear resistant cutting edge (250x25mm, 500HB)
- High wear resistant substructure with several wear stripes (500HB)
- Bucket height 1050mm, bucket depth 1350mm
- With 2 sickle reinforcements
- With 2 hydraulic cylinders
- With adjustable pressure limiting valve
- Opening width ca. 1850mm
- Grapple with 4 bearings
- With side sickles for reduced transport losses

Free selectable colors





SILAGEBUCKET TYPE S XXL

for loader from 5to 8tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Volume	Tines	Weight	Part-No.
2400 mm	3250 l	6	1585 kg	S60 BA-19
2600 mm	3500 l	7	1680 kg	S60 BA-22
2800 mm	3750 l	7	1735 kg	S60 BA-24
3000 mm	4000 l	8	1830 kg	S60 BA-27

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

High wear resistand cutting edge (300x30mm, 500HB) per m.	S3-05
Screwed knife (dbl. bevelded, 250x25mm, 500HB) per m.	S3-20
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)