



The Silagecutter is designed for clean cut of all kinds of silage. The bendsave cutting shield cuts even extrem compressed silage.

AL 178 with heavy duty tines



AL 199 with push-off wall



AL 220



INFORMATION

- Thick material main tube with welded cones
- High value full material tines, 800mm length
- Sidetines with 50mm diameter (S XL)
- Type AL 157 and 178: cranked tines, 2 hydraulic cylinders
- Type AL 199 to 241: HD-tines, 3 hydraulic cylinders, middle knife
- Bend save grapple (max. hydraulic pressure 220 bar)
- Opening width ca. 800mm
- Optional with waved or edged knife (screwed)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



SILAGECUTTER TYPE A L

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Type	Volume	Blockdim.	Tines	Weight	Part-No.
A L 157	1065 l	157x80x80 cm	12	720 kg	S10 BA-41
A L 178	1210 l	178x80x80 cm	14	750 kg	S10 BA-42
A L 199	1350 l	199x80x80 cm	16	990 kg	S10 BA-43
A L 220	1495 l	220x80x80 cm	18	1025 kg	S10 BA-44
A L 241	1640 l	241x80x80 cm	20	1055 kg	S10 BA-45

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Free choice: Waved knife	FM-01
Free choice: Edged knife	FM-02
Heavy duty tines for type A L 157	N8-11 7
Heavy duty tines for type A L 178	N8-11 8
Hydraulic push-off wall for types A L 157 and 178	AW-02s
Hydraulic push-off wall for types A L 199 to 241	AW-02b
Switch valve 12V / 90l (without cable and switch)	UV-02
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)