



Quick info: The Silagecutter is designed for clean cut of all kinds of silage.

Basic equipment



Special: Push-off wall



Cutting process



INFORMATION

- Thick material main tube with welded cones
- High value full material cranked tines, 800mm length
- Sidetines with 50mm diameter (S XL)
- With 2 hydraulic cylinders (max. hydraulic pressure 220 bar)
- Opening width ca. 750mm
- Optional with waved or edged knife (screwed)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



SILAGECUTTER TYPE A S

for loader from 1 to 2,5tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Type	Volume	Blockdim.	Tines	Weight	Part-No.
A S 94	600 l	94x80x75cm	8	450 kg	S05 BA-38
A S 115	730 l	115x80x75cm	9	495 kg	S05 BA-39
A S 136	870 l	136x80x75cm	11	540 kg	S05 BA-40

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Free Choice: Waved knife	FM-01
Free Choice: Edged knife	FM-02
Heavy duty tines for SSZ A S 115	N8-11 5
Heavy duty tines for SSZ A S 136	N8-11 6
Hydraulic push-off wall (+ ca. 120kg, + 1x DA.)	AW-02
Switch valve 12V / 90l (without cable and switch)	UV-02
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)