



Basic equipment, waved knife




Special: Push-off wall, edged knife



The Silagecutter is designed for clean cut of all kinds of silage. The bendsave cutting shield cuts even extrem compressed silage.

Waved / edged knife



INFORMATION

- Thick material main tube with welded cones
- High value full material heavy duty tines, 1000mm length
- Sidetines with 50mm diameter (S XL)
- Extreme strong construction
- Bend save grapple
- Opening width ca. 1300mm
- With 4 hydraulic cylinder (max. hydraulic pressure 220 bar)
- Optional with waved or edged knife (screwed)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



SILAGECUTTER TYPE B - HD

for loader from 6 to 12tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Type	Volume	Bockdim.	Tines	Weight	Part-No.
B 241	2950 l	241x130x95cm	20	2150 kg	S25 BA-45
B 262	3200 l	262x130x95cm	22	2280 kg	S25 BA-46

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Wheel- or telescopic loader	NE-51
-----------------------------	-------

③ SPECIAL EQUIPMENT

Free choice: Waved knife	FM-01
Free choice: Edged knife	FM-02
Hydraulic push-off wall (+ ca. 520kg, + 1x DA.)	AW-02
Switch valve 12V / 180l (without cable and switch)	UV-04
Switch valve 24V / 180l (without cable and switch)	UV-07
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)
--