




The Silagecutter is designed for clean cut of all kinds of silage. The bendsave cutting shield cuts even extrem compressed silage.


Wide opening



Overbite



Waved / edged knife



INFORMATION

- Thick material main tube with welded cones
- High value heavy duty full profile tines, 800mm length
- Sidetines with 50mm diameter (S XL)
- With 2 hydraulic cylinders (max. hydraulic pressure 220 bar)
- Bend save grapple
- Opening width ca. 1200mm
- Optional with waved or edged knife (screwed)

IMPORTANT! The smallest possible working width must be 450mm wider than the width of the quick-coupling-frame of the loader!

Free selectable colors



RAL 7043



RAL 9005



RAL 6011



RAL 2011



SILAGECUTTER TYPE C

for loader from 2,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Type	Volume	Blockdim.	Tines	Weight	Part-No.
C 157	1400 l	157x120x75cm	12	1075 kg	S15 BA-41
C 178	1600 l	178x120x75cm	14	1210 kg	S15 BA-42
C 199	1780 l	199x120x75cm	16	1335 kg	S15 BA-43
C 220	1960 l	220x120x75cm	18	1460 kg	S15 BA-44

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Tail hydraulic cat. II	AF-15
Tail hydraulic cat. III	AF-18
Frontloader without Euro-coupling system	NE-02
Wheelloader with Z-bar Kinematic	NE-59
Wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Free choice: Waved knife	FM-01
Free choice: Edged knife	FM-02
Hydraulic push-off wall (+ ca. 300kg, + 1x DA.)	AW-02
Switch valve 12V / 90l (without cable and switch)	UV-02
Lifting device 1000mm (+ ca. 360kg, 1 x SA., +280 kg)	S01 HH-01
Lifting device 2000mm (+ ca. 440kg, 1 x SA. +440kg)	S01 HH-02
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)