



The Silagecutter with bucket is designed for clean silage stock cutting of each kind in agriculture range. It has a bucket which allows the transport of loose material.


S35 Basic equipment



S36 Basic equipment



Waved / edged knife



INFORMATION

- Highwear resistant cutting edge 500HB
- Strong substructure
- Bucket height 800mm, bucket depth 940mm
- With 1 respectively 2 sickle reinforcements
- With 2 (Type 241 with 3) hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 850mm
- Optional with waved, or edged knife (screwed)



EXPRESS

- Several variants available quickly!



SILAGECUTTER WITH BUCKET S L

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT




Type	Width	Volume	Weight	Part-No.
S L 157	1570 mm	1065 l	750 kg	S35 BA-41
S L 178	1780 mm	1210 l	820 kg	S35.178
S L 199	1990 mm	1350 l	890 kg	S35.199
S L 220	2200 mm	1495	960 kg	S35 BA-44
S L 241	2410 mm	1640 l	1165 kg	S36 BA-45

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheelloader with Z-bar Kinematic	NE-59
All other wheel- or telescopic loader	NE-51

Please indicate **ALWAYS** manufacturer and type of the loader on inquiries or orders!

③ SPECIAL EQUIPMENT

Free choice: Edged knife	FM-02
Free choice: Waved knife	FM-01
 Color RAL 7043 - grey	FA-02
 Color RAL 9005 - black	FA-03
 Color RAL 2011 - orange	FA-05
 Color similar to AGCO grey	FA-11
 Color similar to Fendt nature green	FA-09
 Color similar to MF red	FA-10
 Color similar to John Deere green	FA-07
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)