



The Silagecutter with bucket is designed for clean silage stock cutting of each kind in agriculture range. It has a bucket which allows the transport of loose material.


Basic equipment



Basic equipment



Waved / edged knife



INFORMATION

- Highwear resistant cutting edge 200x20mm, 500HB
- Strong substructure
- Bucket height 1200mm, bucket depth 970mm
- With 1 respectively 2 sickle reinforcements
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 1200mm
- Optional with waved, or edged knife (screwed)



SILAGECUTTER WITH BUCKET S XL

for loader from 2,5to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Type	Width	Volume	Weight	Part-No.
S XL 157	1570 mm	1400 l	1150 kg	S40 BA-41
S XL 178	1780 mm	1600 l	1280 kg	S40 BA-42
S XL 199	1990 mm	1780 l	1400 kg	S40 BA-43
S XL 220	2200 mm	1960 l	1520 kg	S40 BA-44
S XL 241	2410 mm	2140 l	1640 kg	S40 BA-45

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheelloader with Z-bar Kinematic	NE-59
Wheel- or telescopic loader	NE-51

Please indicate **ALWAYS** manufacturer and type of the loader on inquiries or orders!

③ SPECIAL EQUIPMENT

Free choice: Waved knife	FM-01
Free choice: Edged knife	FM-02
■ Color RAL 7043 - grey	FA-02
■ Color RAL 9005 - black	FA-03
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)