



The Silagecutter with bucket is designed for clean silage stock cutting of each kind in


agriculture range. It has a bucket which allows the transport of loose material.



Basic equipment



Waved / edged knife



INFORMATION

- Highwear resistand cutting edge 200x20mm, 500HB
- Strong substructure
- Bucket height 1200mm, bucket depth 970mm
- With 1 respectively 2 sickle reinforcements
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 1200mm
- Optional with waved, or edged knife (screwed)

SILAGECUTTER WITH BUCKET S XL



PRODUCT

for loader from 2,5to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS 0 + 2 + 3 = 3

| CHOOSE PRODUCT | | | | | |
|----------------|---------|--------|---------|-----------|--|
| Туре | Width | Volume | Weight | Part-No. | |
| S XL 157 | 1570 mm | 1400 | 1150 kg | S40 BA-41 | |
| S XL 178 | 1780 mm | 1600 l | 1280 kg | S40 BA-42 | |
| S XL 199 | 1990 mm | 1780 l | 1400 kg | S40 BA-43 | |
| S XL 220 | 2200 mm | 1960 | 1520 kg | S40 BA-44 | |
| S XL 241 | 2410 mm | 2140 | 1640 kg | S40 BA-45 | |

| 2 LOADER QUICK COUPLER (INDICATE BRAND & TYPE) | | | | |
|--|-------|--|--|--|
| Euro-System | AF-M4 | | | |
| Frontloader without Euro-coupling system | NE-02 | | | |
| Wheelloader with Z-bar Kinematic | NE-59 | | | |
| Wheel- or telescopic loader | NE-51 | | | |
| Please indicate ALWAYS manufacturer and type of the loader on inquiries or orders! | | | | |

| SPECIAL EQUIPMENT | |
|--|-------|
| Free choice: Waved knife | FM-01 |
| Free choice: Edged knife | FM-02 |
| Color RAL 7043 - grey | FA-02 |
| Color RAL 9005 - black | FA-03 |
| Pressure limiting valve (needed for pressures above 220 bar) | DB-01 |
| Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.) | DH-01 |

9 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)