




Basic equipment




Basic equipment



The Silagecutter with bucket is designed for clean silage stock cutting of each kind in agriculture range. It has a bucket which allows the transport of loose material.





INFORMATION

- Highwear resistand cutting edge 500HB
- Strong substructure
- Bucket height 800mm, bucket depth 1000mm
- With 1 respectively 2 sickle reinforcements
- With 2 (Type S L 220 and 241 with 3) hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 850mm
- Optional with waved, or edged knife (screwed)

Free selectable colors

RAL 7043 RAL 9005 RAL 6011 RAL 2011

SILAGECUTTER WITH BUCKET TYPE S L



PRODUCT

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS 0 + 2 + 3 = 3

CHOOSE PRODUCT					
Туре	Width	Volume	Weight	Part-No.	
S L 157	1570 mm	1065 l	750 kg	S35 BA-41	
S L 178	1780 mm	1210	820 kg	S35 BA-42	
S L 199	1990 mm	1350 l	890 kg	S35 BA-43	
S L 220	2200 mm	1495 l	1125 kg	S36 BA-44	
S L 241	2410 mm	1640 l	1165 kg	S36 BA-45	

CHOOSE TYPE OF LOADER WITH QUICKCOUPLER				
Euro-System	AF-M4			
Frontloader without Euro-coupling system	NE-02			
Wheelloader with Z-bar Kinematic	NE-59			
All other wheel- or telescopic loader	NE-51			

SPECIAL EQUIPMENT	
Free choice: Waved knife	FM-01
Free choice: Edged knife	FM-02
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

● READY Delivery FCA at factory Visselhövede (Transportcosts on request)