



Opened



Closed



Back view



The Silagecutter with bucket is designed for clean silage stock cutting of each kind in agriculture range. It has a bucket which allows the transport of loose material.

INFORMATION

- Highwear resistant cutting edge 150x20mm, 500HB
- Strong substructure
- Bucket height 600mm, bucket depth 750mm
- With 2 hydraulic cylinders
- Opening width ca. 750mm
- With waved knife (screwed)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



SILAGECUTTER WITH BUCKET TYPE S M

for loader from 1,0 to 2,0tons lifting capacity

A PERFECT ATTACHMENT IN 2 STEPS ① + ② = 😊

① CHOOSE PRODUCT

Type	Width	Volume	Weight	Part-No.
S M 94	940 mm	400 l	450 kg	S30 BA-38
S M 115	1150 mm	490 l	490 kg	S30 BA-39
S M 136	1360 mm	580 l	530 kg	S30 BA-40
S M 157	1570 mm	670 l	570 kg	S30 BA-41

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System (min. width 1150mm)	AF-M4
Frontloader without Euro-coupling system	NE-02
Courtloader with max. 1,5to lifting capacity	NE-41
Wheel- or telescopic loader	NE-51

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)