



**Basic equipment**



**Closed**



**Back view**



*The Silagecutter with bucket is designed for clean silage stock cutting of each kind in agriculture range. It has a bucket which allows the transport of loose material.*

**INFORMATION**

- Highwear resistant cutting edge 150x20mm, 500HB
- Strong substructure
- Bucket height 600mm, bucket depth 750mm
- With 2 hydraulic cylinders
- Opening width ca. 750mm
- With waved knife (screwed)

**Free selectable colors**

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



# SILAGECUTTER WITH BUCKET TYPE S M

for loader from 1,0 to 2,0tons lifting capacity

A PERFECT ATTACHMENT IN 2 STEPS ① + ② = 😊

## ① CHOOSE PRODUCT

| Type    | Width   | Volume | Weight | Part-No.  |
|---------|---------|--------|--------|-----------|
| S M 94  | 940 mm  | 400 l  | 450 kg | S30 BA-38 |
| S M 115 | 1150 mm | 490 l  | 490 kg | S30 BA-39 |
| S M 136 | 1360 mm | 580 l  | 530 kg | S30 BA-40 |
| S M 157 | 1570 mm | 670 l  | 570 kg | S30 BA-41 |

## ② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

|  |       |
|--|-------|
| Euro-System (min. width 1150mm)              | AF-M4 |
| Frontloader without Euro-coupling system     | NE-02 |
| Courtloader with max. 1,5to lifting capacity | NE-41 |
| Wheel- or telescopic loader                  | NE-51 |

## 😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)