




Basic equipment



Basic equipment



Waved / edged knife



The Silagecutter with bucket is designed for clean silage stock cutting of each kind in agriculture range. It has a bucket which allows the transport of loose material.

INFORMATION

- Highwear resistant cutting edge 200x20mm, 500HB
- Strong substructure
- Bucket height 1200mm, bucket depth 1000mm
- With 1 respectively 2 sickle reinforcements
- With 2 hydraulic cylinders (Max. hydraulic pressure 220 bar)
- Opening width ca. 1200mm
- Optional with waved, or edged knife (screwed)

Free selectable colors

■ RAL 7043

■ RAL 9005

■ RAL 6011

■ RAL 2011



SILAGECUTTER WITH BUCKET TYPE S XL

for loader from 2,5 to 6 tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Type	Width	Volume	Weight	Part-No.
S XL 157	1570 mm	1400 l	1150 kg	S40 BA-41
S XL 178	1780 mm	1600 l	1280 kg	S40 BA-42
S XL 199	1990 mm	1780 l	1400 kg	S40 BA-43
S XL 220	2200 mm	1960 l	1520 kg	S40 BA-44

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheelloader with Z-bar Kinematic	NE-59
Wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Free choice: Waved knife	FM-01
Free choice: Edged knife	FM-02
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)