



The Vario snow plough is designed to clean up low till middle snow heights on parking lots and streets.

V - position



1600mm Collect position




3000mm Rear view



INFORMATION

- Each blade half is singularly hydraulic turnable
- With 12V electrical switch valve (1 x DA needed + electrical power line, we recommend to order the cable set together with the blade)
- Hydraulic overlast secure system
- With level adjustment (turnable beared)
- High control with one gliding skid for width to 2200mm. For width from 2600mm with 2 gliding skids (max. speed 35km/h)
- With flapable cutting edge staffed with Special-rubber-blade (150x40mm)
- With position LED-lights and flags

Color  RAL 2011 - orange



- Several variants available quickly!

VARIO SNOW PLOUGH TYPE SPF

for loader from 1,5 to 6tons lifting capacity

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Width	Height	Width (turned 30°/40°/45°)	Weight	Part-No.
1500mm	67/74cm	133/120/ - cm	255kg	W41 BA-10
1750mm	67/77cm	156/139/ - cm	265kg	W41 BA-37
2200mm	79/92cm	191/174/ - cm	435kg	W41 BA-17
2600mm	95/109cm	229/204/189cm	640kg	W41 BA-22
3000mm	95/111cm	263/234/217cm	750kg	W41 BA-27
3400mm	95/113cm	297/266/249cm	815kg	W41 BA-47

② LOADER QUICK COUPLER (INDICATE BRAND & TYPE)

Front hydraulic cat. II	NE-18
Euro-System (incl. level compensation)	NE-00 PF-01
Frontloader without Euro-coupling system (incl. level compensation)	NE-02 PF-01
Courtloader (incl. level compensation)	NE-41 PF-01
Wheel- and telescopic loader (incl. level compensation)	NE-51 PF-01
Connection plate size 3 or 5 (incl. hydr. lifting, +1 DA needed)	NE-B1 PF-02

③ SPECIAL EQUIPMENT

Cable-Set with Switch	W41E-Kit
2 pieces adjustable wheels (instead of gliding skids, for width from 2600mm and more)	V6-S6
Pressure limiting valve (needed for pressures above 220 bar)	DB-01
Pressure holding valve (needed for Bobcat, Dieci, Merlo, MF, aso.)	DH-01

😊 READY (ALL PRICES +7,5% SURCHARGE)

Delivery FCA at factory Visselhövede (Transportcosts on request)