



Working platform manufactured according rules of the german "LSV-Information T01"

### Secured locking



### Save entrance



### safe work



#### INFORMATION

- Individual fitted tubes for pallet fork tines (Please indicate diameter of pallet fork tines)
- With selfclosing and locking door
- Produced according to the "LSV-Information T01"
- With squeeze guard
- Width 1300mm (outside width 1600mm), depth 860mm, height 1100mm
- Lifting capacity 250kg (2 workers + tools)

#### Following points must be fulfilled by the loader:

- The loader must have a save stand
- The loader arm must work parallel automaticly
- Tipping cylinders must be deactivated
- The hydraulic system must be protected against breakings, further is a slow down valve needed.

#### Needed equipment (special equipment):

- By working with motor-saws is a wooden edge guard needed.
- By working under roofs is a squeeze guard needed.

**IMPORTANT:** Please get in contact with your company insurance to check with equipment is demanded and allowed for your country.

- After receiving the working platform you have to make a check-up in connection to the loader.

**Color** ■ RAL 2011 - orange *Stand: 2019 | Our products are distributed by agriculture or building technic dealers | All prices + VAT.*



# WORKING PLATFORM BLA I PG

for pallet forks

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

## ① CHOOSE PRODUCT

Type	Weight	Part-No.
Working plattform BLA I PG	195 kg	H70

## ② CHOOSE PALLET FORK TINE DIAMETER

For pallet fork tines max. 100 x 50 mm	GQ-01
For pallet fork tines max. 130 x 60 mm	GQ-10
For pallet fork tines max. 150 x 70 mm	GQ-02
For pallet fork tines with individuell diameter (indicate measures)	GQ-00

## ③ SPECIAL EQUIPMENT

Wooden edge guard	KS-01
Screwed squeeze guard	SC-01

## 😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)