

PRODUCT
H80



YOUR ATTACHMENT SPECIALIST - www.bressel-lade.de

Send us a mail to: info@bressel-lade.de



Working platform BLA I



Working platform BLA I E



**BLA I with lifting device
HE 16**



Certificated according to EU-Directive 2006/42/EC for all loader-platform-combinations which are listed in the appendix of the certificate. The platform is connected to the loader with the quick-coupling-system of the loader.

INFORMATION


- Lifting capacity 250kg (2 persons + tools)
- With automatically closing and locking door

The loader must fulfill:

- Save stand, • Automatic parallel lift function
- Deactivated tipping function, • Throttled lift function
- Pipe burst security valve on lifting cylinders, • Max. lifting height 10m
- Emergency lowering of the lifting arm and a walkie talkie when lifting height is more than 7,5m

Important: Combinations which are not listed in the [appendix of the certificate](#) must be examined by the DEKRA EXAM. This will cause extra costs.

(*) The offered change-over components (locking valve, oil-flow-limiting valve) are not individual optimized for your loader. We cannot take any warranty for function and compatibility. On demand we will send you information to the specification of the valves. Please get in contact with us.

Color  RAL 2011 - orange

WORKING PLATFORM, WITH EC-GUIDELINE TEST

Certified according to 2006/42/EC

A PERFECT ATTACHMENT IN 3 STEPS ① + ② + ③ = 😊

① CHOOSE PRODUCT

Type	Width (overall)	Depth	Additional height	Weight	Part-No.
BLA I	1300 (1600) mm	860 mm	0 mm	185 kg	BLAI
BLA I E	1300 (1600) mm	860 mm	800 mm	265 kg	BLAIE
BLA I with lifting unit	1300 (1600) mm	860 mm	1600 mm	440 kg	BLAI + HE16
BLA II	2400 (2700) mm	1000 mm	0 mm	345 kg	BLAII

② CHOOSE TYPE OF LOADER WITH QUICKCOUPLER

Euro-System	AF-M4
Frontloader without Euro-coupling system	NE-02
Wheel- or telescopic loader	NE-51

③ SPECIAL EQUIPMENT

Wooden edge guard for BLA I	KS-01s
Wooden edge guard for BLA II	KS-01b
Screwed upper squeeze guard for BLA I	SC-01s
Screwed upper squeeze guard for BLA II	SC-01b
Oil flow limiting valve (electrical for telehandler, 12V HL/HLP 10-250cSt max. 90°C)*	6395
Locking valve (electrical for telehandler needed 2 pieces, 12V HL/HLP 10-250cSt max. 90°C)*	6396
Magnet 12V as spare part*	639003
Electrical switch with keys (for telehandler, 12V)*	6397
EC-guideline-test of a new combination (on request)	6391

😊 READY

Delivery FCA at factory Visselhövede (Transportcosts on request)